
ANTIGOTERAS PINRODA

Technical information



DESCRIPTION

Antigoteras Pinroda is a water-based liquid waterproof coating, which is extremely elastic and is based on a dispersion of acrylic copolymers in emulsion.

TECHNICAL CHARACTERISTICS

Colour: - Terraces: White, black, brick red, rust red, grey and green.

Appearance: Satin

Touch drying : 1 hour approximately.

Coverage: It varies according to type and applications.

Density: 1,3 - 1,4 gr./cm³

Volume of solids: 50% approximately.

Traction resistance: 1,8 Mpa.

Percentage elongation at fracture: 320%

Doubled at -5°C: It doesn't show up cracks.

Do not apply in extreme temperatures or during wet weather.

APLICACIÓN

As a waterproof coating for horizontal surfaces: terraces, coverings and roofs.

In addition, due to its excellent flexibility, resistance to weather and internal cohesion, it is very useful in applications such as:

- Elastic waterproof putty: mixing Antigoteras Pinroda with fine aggregate in a ratio of 1:3.
- Avoid deterioration in the rigid polyurethane foam insulation (Antigoteras Pinroda white).
- Efficient heat insulation due to being an excellent solar ray reflector.

INSTRUCCIÓN FOR USE

GENERAL INSTRUCTIONS FOR USE

• Surface made of concrete, fibre cement, brick, etc. Clean the entire surface carefully to avoid problems with fixing down the product. Loose sand, grease and mildew stains, etc. should be removed. On new concrete or cement you should wait until it has completely set (approximately 30 days).

Apply a first coat of the product that has been well diluted (up to 30%) and if you are dealing with surfaces in poor condition it is advisable to use a fixative such as SELLACRIL. Then continue to apply one or several coats of Antigoteras Pinroda using GLASS FIBRE if required, according to the characteristics of the application, until achieving the recommended thickness.

• Iron and steel surfaces. In addition to cleaning the base carefully, you should apply suitable primers such as: red lead or anti-corrosive primers from the JAFEP range.

- Non-ferrous metal surfaces. Prime prior to application using suitable products such as: wash primer, phosphate primer, etc.
- Wooden surfaces. Clean and sand if required and prepare the surface prior to application with SELLADORA SINTÉTICA JAFEP (ALKYD SEALER)

USE AS A WATERPROOF COATING FOR TERRACES:

In order to achieve the best results from Antigoteras Pinroda we recommend that it be used only on mineral bases (concrete, cement, etc.)..

In addition to all the considerations indicated in the previous section, a thickness of no less than 400 micras must be achieved, which is approximately equivalent to a minimum usage of Antigoteras Pinroda of 1.5 to 2 Kg./m2 and the use of the fibre glass approximately 200 g/m2, as a structural support.

If the flat roof is going to be very well used, you should consult our Technical Department, which will study each case separately.

GUARANTEE

PRODUCTOS JAFEP, s.l. has total confidence in its entire range of products, and it is in those products manufactured, such as Antigoteras Pinroda, that our daily efforts in offering our customers a product that is the leader in its field.

SUBMITTALS

Plastic packaging: 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.