
JAFEP WATER REPELLANT VARNISH

Technical information



DESCRIPTION

Water repellent for exterior faces of concrete, bricks, stone, etc. It does not form a film and maintains porosity. It is water repellent. The appearance of the face does not change, remaining totally invisible when drying.

TECHNICAL CHARACTERISTICS

Nature: Siloxanes diluted in hydrocarbons.
Colour: Transparent.
Density: 0.80 gr./cm³ (approximately).
Drying: 20 - 30 mins.
Application: Brush, roller or spray.
Performance: Very variable depending on the base.
Second coat: At least 24 hours.
Wipedown: Jafep Universal Solvent.

APPLICATION

For making external faces water repellent with the aim of stopping water penetration, but maintaining the unique characteristics of each material and delaying the time it takes to become dirty again.

INSTRUCTIONS FOR USE

Use the product neat without diluting, attempting to completely soak the entire surface to be treated. (1 - 2 m²/litre).

If the surfaces are new: remove dust and loose materials. If it is a concrete surface it will be completely set and free from blooms.

On old surfaces: Remove dirt, dust, loose materials, etc. and if abrasive materials are used, wash and dry.

Do not apply on top of paints.

SUBMITTALS

Metal containers of: 1 Litre; 5 Litres; 20 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.