



LIGNUM NAVY BLUE VARNISH

Technical information

DESCRIPTION

High quality modified alkydic varnish with excellent properties such as: good adherence, penetration and soaking. High level of resistance to environmental and atmospheric agents. High level of flexibility and surface hardness.

TECHNICAL CHARACTERISTICS

Nature: Modified alkydic
Colour: Colourless or transparent
Appearance: Gloss
Density: 1 gr./cm³
Drying: 6-8 hours approximately
Diluent: Jafep Synthetic Solvent
Application: Brush or air gun
Performance: Up to 15 m²/litre and coat

APPLICATION

Varnishing woods, both external and internal, in highly aggressive environments, in coastal areas or in areas with high levels of urban pollution.

INSTRUCTIONS FOR USE

NEW WOOD: Clean, sand it down and remove dust. Apply a first coat diluted 1:10 and sand again. Apply one or more layers undiluted as a finishing coat.

- **VARNISHED WOOD:** Sand until smooth and clean. Apply one or two coats undiluted. If it is in poor condition the existing varnish should be removed and proceed as per the instructions for new wood.

- Cleaning utensils with Jafep synthetic solvent or turpentine.

SUBMITTALS

Metal containers of: 375 ml; 750 ml; 4 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.