



---

## LIGNUM PARQUET VARNISH

### Technical information

---

#### DESCRIPTION

---

Polyurethane varnish for wood subject to high levels of abrasion. Glossy flexible finish. Excellent for brush application and for even finish.

#### TECHNICAL CHARACTERISTICS

---

Nature: Single Part Polyurethane  
Colour: Colourless or transparent  
Appearance: Gloss  
Density: 1 gr./cm<sup>3</sup>  
Drying: 1-2 hours approximately  
Diluent: Jafep Polyurethane Solvent  
Application: Brush or spray.  
Performance: 12 - 14 m<sup>2</sup>/litre and coat

#### APPLICATION

---

For varnishing interior wood subject to constant abrasion, such as parquet flooring, cork flooring, stairs, handrails, etc.

#### INSTRUCTIONS FOR USE

---

- NEW WOOD: Sand it down, clean and apply a first coat (very diluted). Leave for a minimum of 5 hours and a maximum of 24 hours to apply subsequent coats, following a smooth sanding.

- VARNISHED WOOD: Check that it is compatible: sand to a smooth finish and varnish. If the varnishes are not compatible or are do not adhere properly they should be completely removed and you should proceed as per the instructions for new wood.

Cleaning utensils with polyurethane or xylene solvent.

#### SUBMITTALS

---

Metal containers of: 375 ml; 750 ml; 4 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.