



LIGNUM INTERIOR SYNTHETIC VARNISH

Technical information

DESCRIPTION

Synthetic varnish made from alkydic resins, with high levels of adherence, penetration and excellent for brush application. Resistant and quick drying. It has a highly decorative transparent finish.

TECHNICAL CHARACTERISTICS

Nature: Alkydic resins
Colour: Practically colourless
Appearance: Gloss and satin
Density: 1 gr./cm³
Drying: 3-5 hours approximately
Diluent: Jafep Synthetic Solvent
Application: Brush or spray (adjusting density)
Performance: 10 - 14 m²/ litre and coat (depending on finish)

APPLICATION

For varnishing doors, windows, furniture and any wooden surface, for achieving a quality transparent silk finish.

INSTRUCTIONS FOR USE

- NEW WOOD: Clean, sand it down and remove dust. Apply a first coat diluted by 1:10 and sand again. Apply one or more layers undiluted as a finishing coat.
- VARNISHED WOOD: Sand until smooth and clean. Apply one or two coats undiluted. If it is in poor condition the existing varnish should be removed and proceed as per the instructions for new wood.
- Clean utensils with Jafep synthetic solvent or turpentine.

SUBMITTALS

Metal containers of: 375 ml; 750 ml; 4 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.