



---

## **NITROCELLULOSE SOLVENT**

### **Technical information**

---

#### **DESCRIPTION**

---

Solvent especially designed to regulate viscosity and clean tools used with nitrocellulose lacquers and polishes.

#### **TECHNICAL CHARACTERISTICS**

---

Nature: Ketonic solvents, esters, alcohols and aromatic hydrocarbons.

Colour: Colourless.

Appearance: Transparent liquid.

Specific weight:  $0.90 \pm 0.05 \text{ gr./cm}^3$ .

Ignition Temperature: 2.5 °C Method: UNE-EN 456

#### **OBSERVATION**

---

Store completely sealed in its original container under cover and at a temperature of between 5 and 35 °C. Store in ventilated warehouses sheltered from high and low temperatures. Use suitable individual protective measures (masks, goggles, gloves).

Avoid the exposure of containers to high temperatures.

#### **APPLICATION**

---

Viscosity regulator to be applied to nitrocellulose lacquers, nitrocellulose pigmented lacquers and to nitrocellulose products in general.

Specifically for the application of these products by brush, roller or spray. Cleaning tools in the abovementioned products.

#### **SUBMITTALS**

---

Metal containers of: 1 Litre; 5 Litres; 20 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.