



POLYURETHANE SOLVENT

Technical information

DESCRIPTION

Solvent especially designed to regulate viscosity and clean tools used with transparent paint, polyurethane colours and specially designed products.

TECHNICAL CHARACTERISTICS

Nature: Ketonic solvents, esters, alcohols and aromatic hydrocarbons.

Colour: Colourless.

Appearance: Transparent liquid.

Specific weight: $0.90 \pm 0.05 \text{ gr./cm}^3$.

Ignition Temperature: 9.0 °C Method: UNE-EN 456

OBSERVATION

Store completely sealed in its original container under cover and at a temperature of between 5 and 35 °C. Store in ventilated warehouses sheltered from high and low temperatures. Use suitable individual protective measures (masks, goggles, gloves).

Avoid the exposure of the containers to high temperatures.

APPLICATION

Viscosity regulator to be applied to polyurethane paints.

Specifically for the application of these products by brush, roller or spray.

Cleaning tools in the abovementioned products.

Cleaning vessels that contain the catalyst, as indicated in the application. Only for cleaning.

SUBMITTALS

Metal containers of: 1 Litre; 5 Litres; 20 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.