

---

# MATT WATER-BASED EMULSION PAINT “ EasyClean”

---



## Technical Specification

---

### DESCRIPTION

High quality water-based emulsion paint, produced using acrylic emulsion resins. With excellent whiteness, coverage and good performance. For perfect interior and exterior finishes. Its outstanding characteristic is the minimum absorption. It has a wonderful washability and it can easily clean difficult stains (wine, coffee, etc) using a wet cloth and with very few wipes. EasyClean complies with all eco-friendly interior paints requirements, that's why it is being awarded the European Eco-label.

### TECHNICAL CHARACTERISTICS

Nature: Acrylic copolymers  
Colour: White and colours upon request  
Appearance: Matt  
Density: 1,45 gr./cm<sup>3</sup>  
Touch drying: 45 minutes  
Thinner: Water  
Application: Brush, Roller or Spray (adjust viscosity)  
Opacity: 98 %  
Performance: 10-14 m<sup>2</sup>/litro ( UNE- EN ISO 6504-1 : 2007 )  
Recoatable: 6 - 8 hours  
Scrubbability: Class 1 (UNE-EN ISO 11998 : 2007 )  
COV: 10.9 gr/ L.(UNE- EN ISO 11890-2 : 2007)

### APPLICATION

On exterior new surfaces with cement, concrete, fibre cement, etc. and interior surfaces on plaster, prefabricated supports, wood and duly prepared metals support, i.e. Sealer on wood and agglomerate; Primer on iron, plaster and putties. Every support will be clean, dry and cured, free from grease and saltpetre. On new surfaces, apply directly, but thinning down at 10%. Prime previously if it is highly absorbent. Apply directly on painted surface in good conditions, but if not, paint must be removed and proceed like a new surface.

- Do not apply at temperatures below 5 °C.
- Do not expose the packaging to extreme temperatures.

### SUBMITTALS

Plastic packaging: 4 Litres.

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.