

---

## MURALIA UNDERCOATING

### Technical Information

---



#### DESCRIPCIÓN

---

Plastic putty in paste form, ready to use, for apply with trowel or brush and get a rustiuc surface with a very easy application.

#### TECHNICAL CHARACTERISTICS

---

Nature: Vinilyc copolymers

Colour: White

Appearance: Matt

Density: 1.25 gr./cm<sup>3</sup>

Viscosity: Tixotropic

Dry: 6 - 8 hours

Aplication: Trowel

Performance: 1,3 Kg / m<sup>2</sup>

#### APLICACIÓN

---

To apply Muralla Undercoating use a plastering troel. Renderer surfaces roughly to a desired thickness ant textura by keeping the tropel paralel to the wall. Different effects can be obtained by using a brush. In this application it must be diluted with water between 12-15% ant the coverage is greater.

#### INSTRUCTION FOR USE

---

**To non-painted surfaces:** First apply an emulsion undercoat to obtain a surface with a uniform absorption rate.

**Painted surface:** To healthy painted surfaces apply Muralia Undercoating directly . Unfit and unhealthy surfaces should be treated as on-painted surfaces.

#### SUBMITTALS

---

Plastic containers of: 5 and 20 Kg.

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.