



JAFELAC NITROCELLULOSE BASE PRIMER

Technical information

DESCRIPTION

Transparent primer containing nitrocellulose resins combined with alkydic resins. Quick drying and excellent for sanding.

TECHNICAL CHARACTERISTICS

Nature: Nitrocellulose + alkydic

Colour: Colourless

Appearance: Semi-matt

Specific weight: 1.00 ± 0.05 g / cm

Viscosity: 180 ± 30 seconds (Ford Cup n° 4)

Drying: Touch dry in 15 to 20 minutes. Ready for sanding after 2 hours.

Dilution and cleaning: Jafep Nitrocellulose Solvent

Application: Spray and brush.

Performance: 10 - 12 m²/litre

APPLICATION

As a base primer on wooden furniture, frames, doors, windows and any other type of elements of wood carpentry.

INSTRUCTIONS FOR USE

New wood: Clean, sand and remove dust. Apply using thin coats, diluting the product according to whether being applied by brush (5-10%) or spray (20-25%).

The content of the container should be removed properly as this type of combination easily separates into two phases.

Once sanded, ensure that all dust is properly removed and apply the finishing varnishes required.

SUBMITTALS

Metal containers of: 750 ml; 5 Litres; 20 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.