
GHARNATA. Roller Stucco

Technical Information



DESCRIPCIÓN

Decorative coating for interior use, to apply on walls and ceilings of plaster, gypsum and similars, obtaining stucco finishing, inspired by the technique of the “Tadelaket”

TECHNICAL CHARACTERISTICS

Nature: Acrylic Copolimers

Colour: White / Neutral

Appearance: Gloss (alter polishing it)

Density: 1.60 gr./cm³

Viscosity: Tixotrópic Paste

Dry: 6 - 8 hours

Application: Roller, Plastic triangle trowel and stainless steel trowel.

Performance: 2 - 3 m²/Kg.

Tinting: Colourants and “Tinturas Jafep”.

APLICACIÓN

On plaster, gypsum, etc. bases that are clean, dry and free from dust and grease.

INSTRUCTION FOR USE

Different tonalities are obtained by adding our “Tinturas” colourant to the producto.

Easy Application:

The surface must be even, if not, plaster to create a smooth finish with very little absorption. Prime thoroughly using a product such as the Fondo Mate, diluted and coloured using the required shade for the plaster.

Stir vigorously before spreading the product. Apply a thin coat of the product using a roller.

Achieve the final pattern with long and crossed brush strokes with a plastic triangle.

Leave to dry at least 6 hours.

To get the characteristic shiny finish rub and polish using a trowel, and a sanding sheet.

If desired, a protective wax called Ceramul can be applied that protects, improves the resistance to the rubbing and the abrasion and extends the brightness.

SUBMITTALS

Gharnata: Plastic containers: 5 Kg.

Ceramul : Plastic containers: 750 mL.

La información contenida en este documento sirve de guía para el usuario pero no ofrece garantía. Para información relativa a seguridad y medio ambiente consulten la Ficha de Datos de Seguridad.
