



ANTI-CORROSIVE PRIMER

Technical information

DESCRIPTION

Anti-corrosive protector for iron on metal structures, machinery, domestic appliances, etc.
Based on alkydic resins and anti-corrosive pigments capable of offering adequate protection to industrial iron and steel surfaces.

TECHNICAL CHARACTERISTICS

Nature: Alkydic resins
Colour: Red, grey, black, blue, green, orange, white
Appearance: Satin
Specific weight: 1.30 - 1.40 gr./cm³ (depending on colour)
Drying: 2 hours approximately
Diluent: JAFEP Universal Solvent
Application: Brush, roller or spray (adjusting density)
Performance: 8 - 10 m²/kg.
Second coat: 12 hrs

APPLICATION

Primer suitable for painting and for the anti-corrosive protection of all types of internal and external iron and steel surfaces, with excellent adhesion, resistance and durability.

INSTRUCTIONS FOR USE

The surfaces must be degreased, with rust removed, and must be clean and dry. At least 2 thin coats should be applied.

If the surface is still rusty or the paintwork is in poor condition, it should be sanded and the rust removed prior to application of the product.

SUBMITTALS

Metal containers of: 750 ml; 4 Litres; 18 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.