



WATER BASED SWIMMING POOL PAINT

Technical information

DESCRIPTION

Matt emulsion produced using special acrylic resins that have high resistance and durability in terms of the conditions in which they will be used.

TECHNICAL CHARACTERISTICS

Nature: Special acrylic resins
Colour: White and blue
Appearance: Matt
Density: 1.50 g/ cm
Drying: 15 minutes
Diluent: Water
Application: Brush, roller, spray gun, airless gun
Performance: 6 - 8 m²/kg.
Second coat: After 6 hours

APPLICATION

Especially formulated for this particular purpose due to its special resistance to water, alkalis and acids.

INSTRUCTIONS FOR USE

On new concrete and cement surfaces that are clean, dry, and free from dust, rust, grease and saltpetre, apply directly diluting the paint by up to 25% for the first coat. A "Sellacryl" type sealer can also be applied as a primer.

If the surface is already painted with a similar paint and one that is in good condition, sand it prior to application.

Surfaces covered by old paint that is of poor quality or that has not adhered to the surface properly should be removed completely.

In general, we recommend:

- Do not apply at temperatures below 5 °C.
- Do not expose the containers to extreme temperatures.

SUBMITTALS

Metal containers of: 3.5 Litres; 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.