



BRILLOCRIL EMULSION PAINT

Technical information

DESCRIPTION

Gloss emulsion paint with excellent whiteness and coverage. Easy to apply, it provides a finish that is durable, water resistant, easy to wash, resistant to yellowing and that retains a lasting shine.

TECHNICAL CHARACTERISTICS

Nature: Vinyl copolymers

Colour: White

Appearance: Gloss

Specific weight: 1.25 gr./cm³

Drying: 30 - 45 minutes (touch dry)

Diluent: Water

Application: Brush, roller or spray (adjusting density)

Performance: Between 6 and 8 m²/Kg. (depending on the surface)

Tinting: JAFEP Dyestuffs

Second coat: After 6 hours

APPLICATION

Suitable for interior decoration, when dealing with smooth and rough finishes (gotelé, stippled, striped, etc.), giving a glossy appearance, while at the same time long-lasting and very decorative. It provides exteriors with effective protection in all types of finishes.

INSTRUCTIONS FOR USE

On new surfaces that are clean, dry and free from rust and grease made of:

- Cement and concrete: Directly, diluting by up to 25% for the first coat.
- Plaster, gypsums or wood: Fixing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With quality paintwork in good condition: Wash and sand to a smooth finish and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat to begin with using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 7° C.
- Do not expose the containers to extreme temperatures

PRESENTATION

Metal containers of: 750 ml; 4 litres; 8 litres; 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.