

---

# WATER-BASED MATT FINISH EMULSION PAINT DUAL



## Technical Data Sheet

---

### DESCRIPTION

Matt paint with excellent whiteness and coverage. Washable and resistant. Particularly suitable for interior use, but with good performance in exterior use as well thanks to its outstanding resistance and stability.

### TECHNICAL CHARACTERISTICS

Nature: Acrylic copolymers

Colour: White

Appearance: Matt

Density: 1,55 gr./cm<sup>3</sup>

Touch dry: 30 minutes approx.

Thinning: Water

Application: Brush, roller, spray or airless (adjust viscosity)

Coverage: From 5 to 6 m<sup>2</sup>/Kg. (depending on surfaces)

Tinting: JAFEP Dyes

Recoatible: From 2 - 4 hours

### APPLICATION

Paint with high balance properties for a good performance on interior surfaces, walls and ceilings, with easy application and quick touch dry. It can be applied on exterior surfaces like a facade protector in non-extreme conditions.

### INSTRUCTIONS FOR USE

On surfaces that are clean, dry and free from corrosion, grease or saltpetre:

- Cement and concrete: Directly, thinning down the first coat 15% with water.
- Gypsum, plaster or wood: Prime previously with Selladora Sintética (Alkyd Sealer) or with Sellacryl JAFEP.

On painted surfaces:

- On good conditions and high quality paint: wash and sand softly and next, apply it.
- On bad conditions paint: remove it and proceed like a non-painted surface.
- On distempers, PVA and lime paints: Apply a primer or Sellacryl JAFEP.

General recommendations:

- Do not apply at temperatures below 5° C.
- Do not expose the packaging to extreme temperatures.

### SUBMITTALS

Metal packaging: 750 ml; 4 Litres; 8 Litres; 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment. Please consult Safety Data Card.