



---

## **PINKEL STIPPLED EMULSION PAINT**

### **Technical information**

---

#### **DESCRIPTION**

---

Emulsion for interiors. Brilliant white smooth finish. High level of resistance and washability. Especially designed to achieve, using just one product, decorative textured finishes: Stippled, striped, woven, etc.

#### **TECHNICAL CHARACTERISTICS**

---

Nature: Acrylic copolymers

Colour: White

Appearance: Matt

Specific weight: 1.70 gr./ cm

Drying: 1 - 2 hours (touch dry), 24 - 48 hours (totally dry)

Diluent: Water

Application: Depending on type (brush, sponge, comb, etc.)

Performance: Between 0.5 and 3 m<sup>2</sup>/Kg. (depending on application)

Tinting: JAFEP Dyestuffs

#### **APPLICATION**

---

For decorating interiors using a large variety of textured finishes: stippled, woven, gotelé, etc. using in each case the appropriate items: sponge rollers, combs, spatulas, etc.

#### **INSTRUCTIONS FOR USE**

---

On clean new surfaces that are dry and free from rust, grease or saltpetre:

- Cement and concrete: Directly, using the required dilution for each type,
- Plaster, gypsums or wood: Fixing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With quality paintwork in good condition: Wash and seal using a gentle action and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 5° C.
- Do not expose the containers to extreme temperatures

#### **PRESENTATION**

---

Plastic containers of: 4 litres; 18 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.