



---

## **PINRODA STIPPLED EMULSION PAINT**

### **Technical information**

---

#### **DESCRIPTION**

---

Emulsion for interiors. Brilliant white smooth finish. High level of resistance and washability. Especially designed to achieve, using just one product, decorative textured finishes: Stippled, striped, woven, etc.

#### **TECHNICAL CHARACTERISTICS**

---

Nature: Acrylic copolymers.

Colour: White.

Appearance: Matt.

Density: 1.70 gr./ cm

Drying: 1 - 2 hours (touch dry), 24 - 48 hours (totally dry)

Diluent: Water.

Application: Depending on type (brush, sponge, comb, etc.)

Performance: From 0,5 to 3 m<sup>2</sup>/Kg. (depending on application).

Tinting: Jafep dyestuffs.

#### **APPLICATION**

---

For decorating interiors using a large variety of textured finishes: stippled, woven, gotelé, etc. using in each case the appropriate items: sponge rollers, combs, spatulas, etc.

#### **INSTRUCTIONS FOR USE**

---

On clean new surfaces that are dry and free from rust, grease or saltpetre:

- Cement and concrete: Directly, using the required dilution for each type.
- Plaster, gypsums or wood: Fixing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With quality paintwork in good condition: Wash and sand to a smooth finish and apply as follows.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat as a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 5 °C.
- Do not expose the containers to extreme temperatures.

#### **SUBMITTALS**

---

Metal containers of: 18 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.