



EXTRA MATT EMULSION PAINT

Technical information

DESCRIPTION

High quality paint for interiors. With a brilliant white finish, excellent coverage, washable and resistant; it is also suitable for protecting exterior surfaces due to its fastness to light and stability with regard to external atmospheric agents.

TECHNICAL CHARACTERISTICS

Nature: Acrylic copolymers

Colour: White and Black

Appearance: Matt

Specific weight: 1.50 gr./cm³

Drying: 30 - 45 minutes approximately

Diluent: Water

Application: Brush, roller, spray gun or airless gun (adjusting density)

Performance: From 5 to 8 m²/Kg. (depending on the surface)

Tinting: JAFEP Dyestuffs

Second coat: After 5 hours

APPLICATION

For painting interiors: walls and ceilings that require a quality finish, low odour and smooth application. The matt finish is exceptional on all types of surfaces, as is its whiteness and washability.

When applied to exteriors it provides adequate protection to façades due to its excellent resistance to atmospheric agents.

INSTRUCTIONS FOR USE

On new surfaces that are clean, dry and free from rust, grease or saltpetre:

- Cement and concrete: Directly, diluting by up to 10% for the first coat.
- Plaster, gypsums or wood: Fixing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With quality paintwork in good condition: Wash and sand to a smooth finish and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 5° C.
- Do not expose the containers to extreme temperatures.

PRESENTATION

Metal containers of: 750 ml; 4 litres; 8 litres; 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.