



SUPER 86 MATT EMULSION PAINT

Technical information

DESCRIPTION

High quality paint produced using resins and pigments with a high level of resistance and fastness to light. It provides brilliant white washable finishes with excellent coverage.

TECHNICAL CHARACTERISTICS

Nature: Vinyl copolymers

Colour: White

Appearance: Matt

Specific weight: 1.54 gr./cm³

Drying: 30 minutes approximately.

Diluent: Water

Application: Brush, roller, spray gun or airless gun (adjusting density)

Performance: From 5 to 7 m²/Kg. (depending on the surface)

Tinting: JAFEP Dyestuffs

Second coat: From 2 - 4 hours

APPLICATION

Painting and decorating interior and exterior masonry where a quality silk finish that is easy to apply and has a low odour is required.

INSTRUCTIONS FOR USE

On clean new surfaces that are dry and free from rust, grease or saltpetre:

- Cement and concrete: Directly, diluting by up to 15% for the first coat.
- Plaster, gypsums or wood: Fixing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With paints in good condition: Wash and sand to a smooth finish and apply as follows.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 7° C.
- Do not expose the containers to extreme temperatures

PRESENTATION

Metal containers of: 750 ml; 4 litres; 8 litres; 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.