



2000 SATIN EMULSION PAINT

Technical information

DESCRIPTION

High quality emulsion paint for interior and exterior use. High level of stability and resistance, which gives a water-proof and hard-wearing finish with excellent whiteness and good covering power. Final appearance satin / silk. Easy to wash.

TECHNICAL CHARACTERISTICS

Nature: Vinyl copolymers
Colour: White
Appearance: Satin
Specific weight: 1.25 gr./cm³
Drying: 30 - 45 minutes (touch dry)
Diluent: Water
Application: Brush, roller, spray gun or airless gun (adjusting density)
Performance: 5 - 8 m²/kg.
Tinting: JAFEP Dyestuffs
Second coat: After 6 hours

APPLICATION

Quality paint. Excellent results in terms of whiteness, coverage and washability on all types of surfaces, walls and ceilings, leaving a pleasing satin / silk appearance on both smooth and rough surfaces (gotelé, stippled, striped, etc.), and effective protection to exteriors.

INSTRUCTIONS FOR USE

On new surfaces that are clean, dry and free from rust and grease made of:

- Cement and concrete: Directly, diluting by up to 25% for the first coat.
- Plaster, gypsums or wood: Sealing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With quality paintwork in good condition: Wash and sand to a smooth finish and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 7 °C.
- Do not expose the containers to extreme temperatures.

PRESENTATION

Metal containers of: 750 ml; 4 litres; 8 litres; 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.