



PINRODA PLAIN COATING

Technical information

DESCRIPTION

Matt covering formulated using acrylic copolymers, pigments and gums, with a high level of resistance and fastness; with good resistance to the weather, to saltpetre and to abrasion, which gives it excellent results outdoors in moderately aggressive atmospheric environments.

TECHNICAL CHARACTERISTICS

Nature: Acrylic copolymers.

Colour: White and others to order.

Appearance: Silk matt.

Specific weight: 1.60 gr./cm³

Drying: 30 minutes.

Diluent: Water.

Application: Brush, roller, spray gun.

Performance: 4 - 6 m²/kg.

Second coat: After 4 hours.

Tinting: Jafep dyestuffs.

APPLICATION

For decorating and protecting exteriors, façades, yards, exterior walls, etc.

INSTRUCTIONS FOR USE

- On new surfaces that are clean, dry and free from rust, grease or saltpetre, if they are made of concrete or cement, apply directly, diluting by up to 20% for the first coat. If the surfaces are made of plaster, gypsum, etc. they must be sealed prior to application.
- On old painted surfaces in good condition, wash, sand to a smooth finish and then apply. If they are in poor condition, remove and proceed as per the instructions for new surfaces.

SUBMITTALS

Metal containers of: 3.5 Litres 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.