

REVESTIMIENTO LISO PETREX 5 SILICONADO (SMOOTH SILICONED COATING)

Technical specification

DESCRIPTION

Exterior coating based on polysiloxane formulation. With good resistance to harsh weather, salpeter and abrasion. Waterproof and mouldproof. The polysiloxane provides a water-repellent effect as well, and make the permeability to water-vapour easier at the same time.

TECHNICAL CHARACTERISTICS:

Nature: Acrylic copolymers and polysiloxane resins.
Colours: White and colours to order
Appearance: Smooth matt
Density: $1.5 \pm 0,5$ gr./ cm³
Drying: 45 minutes approximately.
Recoatable about 5h
Thinning: Water
Application: Brush, roller, spray or airless (adjust viscosity)
Coverage: From 10 to 12 m²/L, and coat (depending on the surfaces).
Colours: Colorantes JAFEP (JAFEP dyes)

APPLICATION

Exterior decoration and protection: Exterior walls, courtyards, etc. with an excellent quality finish and unbeatable washability and coverage.

INSTRUCTIONS FOR USE

On exterior surfaces that are clean, dry and free from corrosion, grease, paint in bad condition or saltpetre

- Apply directly but thin down to 10% for the first coat. Then, apply a second coat with a slight thinning down.
- On old painted surfaces: Remove the paint in bad conditions using water under pressure and make the required repairs. With mould, use bleach to remove them, rinse and dry.

General recommendations:

- Do not apply at temperatures below 5° C.
- Do not apply if it is possible to rain.
- Do not expose the packaging to extreme temperatures.

SUBMITTALS

Metallic packaging: 15 litres.

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.

