



---

## **PINRODA TEXTURED COATING**

### **Technical information**

---

#### **DESCRIPTION**

---

Textured petreous coating produced using resins in emulsion and pigments. It has a high level of resistance and fastness to light, which provides an elastic, water resistant finish but at the same time resistant to adverse climatological agents. It has excellent filling power, which conceals defects in mortar and excellent stippling, with a textured brilliant white finish. Easy to apply.

#### **TECHNICAL CHARACTERISTICS**

---

Nature: Copolymers in emulsion.  
Colour: White.  
Appearance: Matt.  
Specific weight: 1.70 gr./ cm  
Drying: 30 minutes (touch dry)  
Diluent: Water.  
Performance: 1 m<sup>2</sup>/Kg. (varies depending on surface)  
Second coat: After 6 hours.

#### **APPLICATION**

---

Petreous coating suitable for protecting façades, interior patios, in moderate climates.

#### **INSTRUCTIONS FOR USE**

---

It can be applied by brush, roller or spray gun to create gotelé and tyrolean effects. The surfaces must be clean, dry and free from rust, saltpetre, damp, etc. If the surface is new it should be primed with a coat of paint diluted with 10-15% water, followed by an other coat to be applied neat in order to achieve the desired effect.

If the surface is old, and is already painted, you should try scraping and cleaning the parts which are in poor condition completely.

Do not apply below 5 °C.

#### **SUBMITTALS**

---

Metal containers of: 3.5 Litres 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.