



---

## THIXOTROPIC SYNTHETIC SEALER

### Technical information

---

#### DESCRIPTION

---

This is a thixotropic primer/sealer formulated using special alkyd resins and pigments with a high level of resistance and fastness, which prepares surfaces for filling, sealing and covering them effectively. It is easy to apply and cover, and can be sanded thoroughly so as to obtain flat and polished surfaces.

#### TECHNICAL CHARACTERISTICS

---

Nature: Alkyd

Colour: White

Appearance: Satin

Drying: 1 - 2 hours (touch dry)

Diluent: Aliphatic (White Spirit)

Application: Brush or woollen roller and spray (adjusting density)

Performance: 5 - 7 m<sup>2</sup>/kg. depending on the porosity of the surface

Second coat: 12 hrs

Viscosity: Thixotropic

#### APPLICATION

---

It is an ideal sealer for priming and sealing porous wooden, plaster or gypsum surfaces. It covers and isolates stains caused by smoke, soot, etc.

#### INSTRUCTIONS FOR USE

---

Remove the content of the container. Apply using a brush and roller in its original consistency or by diluting it with a suitable diluent (White Spirit, turpentine, etc.) by 5-10%. If applied using a spray gun you should adjust the product density to suit.

Surfaces must be clean and dry and free from rust, dust, grease, saltpetre, damp, etc.

Surfaces that contain previous coats of paintwork should be scraped and cleaned completely in order to ensure the adhesion to these previous coats.

Apply one or two layers, leaving to dry completely and sanding it as required between applications.

#### SUBMITTALS

---

Metal containers of: 750 ml; 4 Litres; 18 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.