

## TELACRIL RUGOSO FACHADAS (ROUGH EXTERIOR WALL)

### Technical specification

#### DESCRIPTION

Rough coating, matt and decorative finish, anti fracture and waterproof, produced using special acrylic resins as a base, which give it extraordinary elasticity and flexibility, even at extreme low temperatures, and a total waterproofing on vertical surfaces.

#### TECHNICAL CHARACTERISTICS:

Nature: Acrylic  
Colour: White and colours to order.  
Appearance: Matt  
% weight of solids: 77,4 (approx.)  
% volume of solids: 62,5 (approx.)  
Viscosity : Thixotropic  
Density: 1,55 + 0,05 gr./cm<sup>3</sup> (at 23 +2°C)  
PH: 9 + 1 (at 23 +2 ° C)  
Drying: 2 hours (approximately)  
Thinning and cleaning: Water  
Application: Brush, roller or spray  
Coverage: 2 - 4 m<sup>2</sup>/Kg (by coat depending on surface)  
Tinting: Colorante Jafep (dye)

#### INSTRUCTIONS FOR USE

Product specifically designed to protect and waterproof exterior walls which require both elastic and structured finish because of fractures or future possible fractures.

On new surfaces that are clean, dry and free from rust, grease or saltpetre of cement and concrete: Apply directly but thin down to 50% with water for the first coat. Another effective primer would be SELLACRYL JAFEP, but thinning down with water in 1:3 proportion.

On painted surface in good condition and quality: wash, sand and apply directly or with a initial thinning down to 10-15%.  
On painted surface in bad condition, remove and proceed like a new surface.

- Do not apply at temperatures below 5° C.
- Do not expose the packaging to extreme temperatures.

#### SUBMITTALS

Metallic packaging: 15 Litres

The information contained in this document serves as a guide for the user but offers no guarantee. For information relating to safety and the environment, please consult the Safety Data Card.

