

## Ficha Técnica

# Paint with Antibacterial preservative with EasyClean Technology

Acrylic plastic paint with antimicrobial preservative

Versión: 25/11/2019



## Ventajas

- Easy cleaning
- Not absorbent

## Descripción

Water-based paint of great coverage and excellent finish, for interior wall and ceiling painting. Thanks to the incorporation of an antimicrobial preservative prevents the development of bacteria that are deposited in the paint. It is an ideal product for any place where it is sought that the surfaces remain cleaner and hygienic even after numerous washes, such as hospitals, operating rooms, nurseries, geriatric centers, kitchens, etc.

### Antimicrobial preservative:

The preservative with silver ions has proven its effectiveness against the main bacteria present in our environment, such as Salmonella, E.Coli, Legionella and a broad spectrum of up to more than 50 known bacteria. It is durable and very active, so that when incorporated, it remains effective throughout the life of the paint.

### EasyClean Technology:

Our exclusive technology developed by Jafep greatly prevents the absorption of dirt inside the paint layer, thus facilitating cleaning with a simple pass of a damp cloth and without the need to rub. In combination with the antimicrobial preservative, it makes it one of the most hygienic alternatives to cover walls and ceilings of any room.



## Propiedades

Easy to apply paint. Excellent finish and great covering power. It incorporates in its formulation an antibacterial preservative that prevents the growth of bacteria by promoting a cleaner environment. Its high quality finish gives it high washability and whiteness.

## Certificados de empresa



## Datos técnicos

### Datos de identificación del producto

Color	White & colours on request
Naturaleza	Acrylic copolymers
Peso específico	1,45 ± 0.05 g/cm <sup>3</sup>
Viscosidad	8.500 ± 1000 cp (en Brookfield)

### Datos de aplicación del producto

Herramienta	Brush, roller, gun or airless
Rendimiento	10-14 m <sup>2</sup> /L/coat
Diluyente	Diluent for water-based paints and enamels
Repintado	6 - 8 hours
Secado	45 minutes
Curado	28 days

### Prestaciones finales



Resistencia al frote en húmedo

Class 1 (Norm UNE-EN 13300); >10000 cycles (Norm DIN 53778)

Aspecto Aplicado

Matte

## Dónde aplicarlo

On new surfaces of cement, concrete, fiber cement, etc. and interiors of plaster, prefabricated, wood and metals treated properly, as for example: Sealer in wood and agglomerates; Primer on iron; Fixing background on plaster and putties.

## Precauciones

- Do not apply at temperatures below 5 ° C or above 30 ° C.
- Do not apply with risk of frost or rain.
- Do not apply in strong wind conditions or in direct sun.
- Avoid using different batches in the same cloth or, failing that, mix the current canister with the next one at 50% to reduce the normal differences between batches.

## Modo de empleo

ON NEW CLEAN, DRY AND EXEMPT SURFACES OF OXIDE, FAT OR SALITRE OF:

Cement and concrete: Once set. Directly, diluting up to 10% for the first layer.

Plaster, plaster or wood: Fixing or sealing previously with appropriate products for each case. Diluting up to 10% in the first hand.

ON PAINTED OLD SURFACES:

With paints in good quality: Wash and sand gently, putty if necessary and then apply.

With paintings in poor condition: Remove and proceed as a new surface. If alkalinity is detected in the support, it must be corrected.

## Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

## Formatos

4L and 15L cans



# Memoria descriptiva

## ***In simple applications***

The painting and / or decoration, in interior, of masonry surfaces will be done with the paint with antibacterial preservative of the company Pinturas Jafep. The yield will be from 10 to 14 m<sup>2</sup> / L and layer. The support must be clean, dry and free of rust, dust, grease, salt and moisture. The manufacturer's general recommendations will be respected.



*Atención al Cliente*

**967 44 05 96**

atencionalcliente@jafep.com



*Servicio Técnico*

**dpto\_tecnico@jafep.com**

