

# Ficha Técnica

## Tile Paint

Tile Alkyd Satin Enamel

Versión: 17/03/2020



## Descripción

Tile Satin Enamel for direct application without the need for a primer. Excellent anchorage and resistance to rubbing. Provides a ceramic finish and great color retention. Washable and has an unalterable finish.

## Propiedades

- Finishes of great finesse.
- Excellent surface protection.
- Excellent anchorage
- High resistance to friction
- Washable

## Certificados de empresa



## Datos técnicos

### Datos de identificación del producto

Color	Ivory, Sky, Dolphin Gray and Zen
Aspecto	Satin
Naturaleza	Resinas alquídicas uretanadas
Peso específico	1.10 - 1.4 Kg / L (depending on color)

### Datos de aplicación del producto

Rendimiento	12 -14 m <sup>2</sup> /L/Coat
Diluyente	Jafep Synthetic Solvent
Repintado	24 hours
Secado	4 - 6 hours

## Dónde aplicarlo

For indoor and outdoor use. Indicated for tile painting, featuring a high lime satin finish

## Precauciones

- Do not apply at temperatures below 5 °C nor above 30 °C.
- Do not apply with risk of frost or rain.
- Do not apply in strong winds or under direct sun.
- Avoid using different batches on the same cloth or, failing that, mix the current pot with the next one at 50% to reduce the normal differences between batches.

## Productos relacionados

SYNTHETIC SOLVENT

## Modo de empleo

Thoroughly clean the area where the enamel will be applied, using water and a non-greasy soap. Take special precaution to avoid waxes and silicones.



Cleaning of the tile joints must be carried out in depth, using a brush in order to remove any remaining dirt, grease or mold. In the case of finding mold, apply Jafep Mold Cleaner according to its instructions.

The entire cleaned surface must be thoroughly rinsed and thoroughly dried before starting the painting.

Product practically to use. It can be diluted to improve its brushability. Stir the content vigorously until it is completely homogenized.

It can be applied with a brush, roller or spray gun, always in thin layers and respecting repainting times. The application temperature, humidity and thickness and type of substrate are associated with changes in drying time and theoretical performance.

To clean the tiles: A couple of days after the application, you can take a cloth with water to clean the tiles, and after a week you could use a mild soap. It is important not to use abrasive elements to avoid scratching the surface.

**WARNINGS:** When used near sources of intense heat (glass ceramic, stove, etc.) it may cause yellowing.

## Almacenamiento

- In its original closed container, at not extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

## Formatos

750 ml metal pot



*Atención al Cliente*

**967 44 05 96**

atencionalcliente@jafep.com



*Servicio Técnico*

dpto\_tecnico@jafep.com

