

Ficha Técnica

Alkyd Gloss Enamel



Descripción

This is a high gloss synthetic enamel which has excellent coverage, formulated using special alkyd resins and pigments containing contrasting resistance and stability to light, which gives optimum quality finishes. It is a product developed with the technique "high solids", that's why it is recommended to apply thin coats and to respect the drying and recoatable times in order to get the best benefits.

Datos técnicos

Datos de identificación del producto

Color	Depending on colour chart
Aspecto	Gloss
Peso específico	between 0,95gr./ cm3 and 1,25 gr./cm3 depending on colour.

Datos de aplicación del producto

Rendimiento	12 - 14 m2/litre depending on the state of the surface.
Repintado	24 hours
Secado	4 - 6 hours



Dónde aplicarlo

Iron, Steel, Wood, Plaster, etc.

It is a high quality synthetic gloss enamel, which covers the needs of the professional painter and housewife, being extremely suitable for decorating and protecting surfaces made of iron, steel, wood, plaster, etc., such as: doors, chairs, tables, windows, radiators, railings, metal structures, machinery, boats, etc.

The practical spreading rate will depend on the actual dry film thickness, the nature of the substrate and the application method.

Modo de empleo

Stir the content of the packaging. Apply by brush or roller with the original viscosity. If it is applied by spray gun, adjust viscosity with the suitable solvents. If the surface is already painted, scraped and clean in order to ensure the adhesion to these previous coats.

When applying to wood and plaster, the surface should be prepared beforehand using a suitable sealer, such as : Selladora Sintética (Alkyd Sealer) or Multiusos al agua (Water-based multipurpose primer)

When applying to iron and steel, the surface should be protected beforehand using Imprimación Antioxidante (Anticorrosive primer) or Minio de Plomo (Red Lead). On galvanised steel and alloys, duly prime beforehand.

As it is a high solid product, in interior use, it could be enough with just one coat of enamel. In exterior use, it is recommendable to finish with 2 or 3 coats.

Formatos

Metallic packaging: 125 ml; 375 ml; 750 ml 4 Liters;



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado
Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com