

Ficha Técnica

Pinroda Low Cost

Matt Pinroda Low Cost Acrylic Paint

Versión: 23/10/2020



Ventajas

- High whiteness
- Good coverage
- Unbeatable quality price ratio

Descripción

Water-based acrylic matt paint for interiors with high whiteness and coverage. Unbeatable quality price ratio.

Certificados de empresa



Datos técnicos

Datos de identificación del producto



Color	White
Aspecto	Matt
Naturaleza	Acrylic Copolymers
Peso específico	1.65 gr./cm ³

Datos de aplicación del producto

Herramienta	Brush, Roller Spray Gun, Airless
Rendimiento	6 - 8 m ² / Liters/Coat
Diluyente	Water
Repintado	4-5 hours
Secado	30 minutes

Prestaciones finales

Resistencia al frote en húmedo	Class 5 UNE 13300 (>300 cycles, UNE 48243)
--------------------------------	--

Dónde aplicarlo

Brush, roller or gun (adjusting viscosity)

Economic paint for interiors, ideal for painting ceilings, with good performance, whiteness and covering.

The practical performance (actual) will depend on the thickness of the film, the nature of the substrate and the method of application.

Precauciones

- Do not apply at temperatures below 5 °C nor above 30 °C.
- Do not apply with risk of frost or rain.
- Do not apply in strong winds or under direct sun.
- Avoid using different batches on the same cloth or, failing that, mix the current pot with the next one at 50% to reduce the normal differences between batches.

Productos relacionados

SELLACRYL



Modo de empleo

On all kind of surfaces that are duly clean, dry, set and free from grease:

- On new concrete or plaster surfaces: Apply directly but dilute to 25% for the first coat.
- On old painted surface in good condition: Wash, and sand previously. On old painted surface in bad condition: Remove and proceed like a new surface. Even sanding: Apply a primer undercoat or Sellacryl JAFEP.

Almacenamiento

- In its original closed container, at not extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Format: 3 and 14 litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA

DUBAI

ESPAÑA

MARRUECOS

POLONIA

UCRANIA



www.jafep.com
jafep@jafep.com