

Ficha Técnica

Acrimar Water-based Acrylic Enamel with Polyurethane



Water-based acrylic enamel.

Versión: 20/03/2023



Ventajas

- Easy application.
- Good leveling.

Descripción

Water-based acrylic enamel of easy application and very good leveling. Washable, odorless and non-flammable. Does not yellow. It offers extraordinary hardness and resistance to friction.

Certificados de empresa



Datos técnicos

Datos de identificación del producto



Color	Gold, Silver (metallic finish), White, Black, Satin Acrimar color chart and bases of the MCS system
Aspecto	Metallic, Glossy, Satin, and Mat
Naturaleza	Acrylic copolymers

Datos de aplicación del producto

Herramienta	Brush, roller, spray or airless
Rendimiento	12 – 14 m ² /L/layer
Diluyente	Thinner for water-based paints and enamels
Repintado	6 hours
Secado	1 Hour

Prestaciones finales

Resistencia al frote en húmedo	5
--------------------------------	---

Dónde aplicarlo

Applicable both indoors and outdoors. Very suitable for decorating and protecting surfaces made of iron, wood, plaster, etc., such as doors, chairs, tables, windows, walls, furniture, railings, metal structures, etc. And of course kitchens and bathrooms.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current can with the next at 50% to reduce the normal differences between batches.

Modo de empleo

Stir the contents of the container well. Apply by brush, roller or spray to clean, dry, dust-free and properly prepared surfaces.

PAINTED SURFACE: If the surface is in good condition, wash, sand and directly apply Acrylic Enamel to Acrimar Water. Otherwise, completely remove the old paint and proceed as unpainted surface.



UNPAINTED SURFACES:

Wood: Apply a coat of Multipurpose water-based or Water-based Sealant.

Metal: Apply a layer of Multipurpose or water-based antioxidant primer.

Walls: Apply "Acrimar" directly or prepare with Sellacryl.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep out of direct sunlight.
- Maximum recommended since manufacture: 2 years.

Carta de colores

Check Acrimar Satin Color Chart

Formatos

Containers of: 250 ml, 750 ml, 4L e 15L



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com

