

Ficha Técnica

ANTIGOTERAS PINRODA



Descripción

Antigoteras Pinroda is a water-based liquid waterproof coating, which is extremely elastic and is based on a dispersion of acrylic copolymers in emulsion.

Datos técnicos

Datos de identificación del producto

Color	White, black, brick red, rust red, grey and green.
Aspecto	Satin
Peso específico	1,3 - 1,4 gr./cm ³

Datos de aplicación del producto

Rendimiento	It varies according to type and applications
Secado	1 hour approximately



Dónde aplicarlo

As a waterproof coating for horizontal surfaces: terraces, coverings and roofs.

In addition, due to its excellent flexibility, resistance to weather and internal cohesion, it is very useful in applications such as:

- Elastic waterproof putty: mixing Antigoteras Pinroda with fine aggregate in a ratio of 1:3.
- Avoid deterioration in the rigid polyurethane foam insulation (Antigoteras Pinroda white).
- Efficient heat insulation due to being an excellent solar ray reflector.

Productos relacionados

SELLACRYL
THIXOTROPIC SYNTHETIC SEALER

Modo de empleo

- Surface made of concrete, fibre cement, brick, etc. Clean the entire surface carefully to avoid problems with fixing down the product. Loose sand, grease and mildew stains, etc. should be removed. On new concrete or cement you should wait until it has completely set (approximately 30 days).

Apply a first coat of the product that has been well diluted (up to 30%) and if you are dealing with surfaces in poor condition it is advisable to use a fixative such as SELLACRYL. Then continue to apply one or several coats of Antigoteras Pinroda using GLASS FIBRE if required, according to the characteristics of the application, until achieving the recommended thickness.

- Iron and steel surfaces. In addition to cleaning the base carefully, you should apply suitable primers such as: red lead or anti-corrosive primers from the JAFEP range.

Productos JAFEP, S.L. Carretera de Barrax, s/n
02630 La Roda (Albacete) España

Tel.: 967 44 05 96 – 967 44 00 36 – 967 44 06 45 Fax: 967 44 26 12 E-mail: dpto_tecnico@jafep.com

- Non-ferrous metal surfaces. Prime prior to application using suitable products such as: wash primer, phosphate primer, etc.

- Wooden surfaces. Clean and sand if required and prepare the surface prior to application with SELLADORA SINTÉTICA JAFEP (ALKYD SEALER)

Formatos

Plastic packaging: 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado
Compromiso Medioambiental y Social Jafep

