

Ficha Técnica

BRILLOCRIL EMULSION PAINT



Descripción

Gloss emulsion paint with excellent whiteness and coverage. Easy to apply, it provides a finish that is durable, water resistant, easy to wash, resistant to yellowing and that retains a lasting shine.

Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Gloss
Naturaleza	Vinyl copolymers
Peso específico	1.25 gr./cm ³

Datos de aplicación del producto

Rendimiento	Between 6 and 8 m ² /Kg. (depending on the surface)
Diluyente	Water
Repintado	After 6 hours



Secado

30 - 45 minutes (touch dry)

Dónde aplicarlo

Brush, roller or spray (adjusting density).

Suitable for interior decoration, when dealing with smooth and rough finishes (gotelé, stippled, striped, etc.), giving a glossy appearance, while at the same time long-lasting and very decorative. It provides exteriors with effective protection in all types of finishes.

Productos relacionados

SELLACRYL
THIXOTROPIC SYNTHETIC SEALER

Modo de empleo

On new surfaces that are clean, dry and free from rust and grease made of:

- Cement and concrete: Directly, diluting by up to 25% for the first coat.
- Plaster, gypsums or wood: Fixing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With quality paintwork in good condition: Wash and sand to a smooth finish and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat to begin with using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 7° C.
- Do not expose the containers to extreme temperatures

Formatos

Metal containers of: 750 ml; 4 litres; 8 litres; 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com