Ficha Técnica

EXTRA MATT EMULSION PAINT





Descripción

High quality paint for interiors and also for exterior protection. With a deep, very white extra matt finish, as well as covering, washable and resistant. It conceals imperfections and has a dotted bass.

Datos técnicos

Datos de identificación del producto

Color	White and Black
Aspecto	Matt
Naturaleza	Acrylic copolymers
Peso específico	1.50 gr./cm3

Datos de aplicación del producto

Rendimiento	From 5 to 8 m2/Kg. (depending on the surface)
Diluyente	Water
Repintado	After 5 hours



Dónde aplicarlo

Brush, roller, spray gun or airless gun (adjusting density).

For painting interiors: walls and ceilings that require a quality finish, low odour and smooth application. The matt finish is exceptional on all types of surfaces, as is its whiteness and washability. When applied to exteriors it provides adequate protection to façades due to its excellent resistance to atmospheric agents.

Productos relacionados

THIXOTROPIC SYNTHETIC SEALER SELLACRYL

Modo de empleo

On new surfaces that are clean, dry and free from rust, grease or saltpetre:

- Cement and concrete: Directly, diluting by up to 10% for the first coat.
- Plaster, gypsums or wood: Fixing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With quality paintwork in good condition: Wash and sand to a smooth finish and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.
- In general, we recommend:
- Do not apply at temperatures below 5° C.
- Do not expose the containers to extreme temperatures.

Formatos

Metal containers of: 750 ml; 4 litres; 8 litres; 15 Litres







jafep@jafep.com