

## Ficha Técnica

# JAFEP WATER REPELLANT VARNISH



## Descripción

Water repellent for exterior faces of concrete, bricks, stone, etc. It does not form a film and maintains porosity. It is water repellent. The appearance of the face does not change, remaining totally invisible when drying.

## Datos técnicos

### Datos de identificación del producto

Color	Transparent.
Naturaleza	Siloxanes diluted in hydrocarbons
Peso específico	0.80 gr./cm <sup>3</sup> (approximately).

### Datos de aplicación del producto

Rendimiento	Very variable depending on the base.
Repintado	At least 24 hours.
Secado	20 - 30 mins.



## Dónde aplicarlo

Brush, roller or spray.

For making external faces water repellent with the aim of stopping water penetration, but maintaining the unique characteristics of each material and delaying the time it takes to become dirty again.

## Modo de empleo

Use the product neat without diluting, attempting to completely soak the entire surface to be treated. (1 - 2 m<sup>2</sup>/litre).

If the surfaces are new: remove dust and loose materials. If it is a concrete surface it will be completely set and free from blooms.

On old surfaces: Remove dirt, dust, loose materials, etc. and if abrasive materials are used, wash and dry. Do not apply on top of paints.

## Formatos

Metal containers of: 1 Litre; 5 Litres; 20 Litres



*Atención al Cliente*

**967 44 05 96**

[atencionalcliente@jafep.com](mailto:atencionalcliente@jafep.com)



*Servicio Técnico*

**dpto\_tecnico@jafep.com**



Compromiso Medioambiental y Social Jafep

100% Reciclado

