Ficha Técnica

PETREX 5 PLAIN COATING





Descripción

Exterior coating. Water-proof and washable. High level of resistance to weather, saltpetre and abrasion. It has I.N.C.E. certification

Datos técnicos

Datos de identificación del producto

Color	White and all the colours from the sample colour chart
Aspecto	Matt
Naturaleza	Acrylic copolymers
Peso específico	1.35 +- 0.3 gr./ cm

Datos de aplicación del producto

Rendimiento	Between 5 and 8 m2/kg. (depending on the surface)
Diluyente	Water
Repintado	After 5 hours



Dónde aplicarlo

Brush, roller, spray gun or airless gun (adjusting density).

For decorating and protecting exteriors: façades, yards, exterior walls, etc.; but also, due to its extraordinary smoothness, it can be used to decorate interiors, particularly in pastel shades, with a magnificent quality washable finish and unbeatable performance.

Productos relacionados

THIXOTROPIC SYNTHETIC SEALER SELLACRYL

Modo de empleo

On clean new surfaces that are dry and free from rust, grease or saltpetre:

- Cement and concrete: Directly, diluting by up to 20% for the first coat.
- Plaster, gypsums or wood: Sealing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.
- Powdery surfaces, first apply a base coat using fixative.

On old painted surfaces:

- With quality paintwork in good condition: Wash and sand to a smooth finish and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.
- In general, we recommend:
- Do not apply at temperatures below 5° C.
- Do not expose the containers to extreme temperatures.

Formatos

Metal containers of: 3.5 Litres 15 Litres







jafep@jafep.com