

Ficha Técnica

PETREX 5 TEXTURED COATING



Descripción

This is a rough petreous coating especially for façades, based on acrylic resins and pigments. It has a high level of resistance and fastness to light, which provides hard, elastic, water resistant finishes with excellent coverage and filling power.

Datos técnicos

Datos de identificación del producto

Color	Depending on colour chart
Aspecto	Matt

Datos de aplicación del producto

Rendimiento	1 m ² /Kg. (depending on condition of surface)
Diluyente	Water
Repintado	From 2 - 4 hours
Secado	30 minutes approximately



Dónde aplicarlo

It can be applied by brush, roller or spray gun to create gotelé and tyrolean effects. It is a petreous covering suitable for protecting façades. Also suitable in adverse climates.

Modo de empleo

It can be applied by brush, roller or spray gun to create gotelé and tyrolean effects. The surfaces should be clean, dry and free from rust, dust, grease, saltpetre, damp, etc. Hard surfaces or those that contain old paints should be scraped and cleaned completely, applying a first coat diluted by 10 to 15% water, and a second coat neat in order to achieve the required textured effect. Do not apply at temperatures below 5° C.

Formatos

Metal container of: 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com

