

Ficha Técnica

PETREX Mortero Acrílico (Acrylic Mortar)



Descripción

This is a stone coating type mortar, thick coat, especially developed for exterior and interior walls, based on all acrylic resins and pigments with high resistance and stability to light. It provides hard, elastic, waterproof, great coverage and filling. The granulometry of its extenders is prepared to get striped finish.

We have two finishes: Thick (arid to 2 mm)

Thin (arid to 1 mm)

Datos técnicos

Datos de identificación del producto

Color	Depending on colour chart
Aspecto	Matt Filler

Datos de aplicación del producto

Rendimiento	Thin 0.5 m ² / Kg. (It is required from 1.8 tp 2 kg for 1 m ² os standard surface) Thick 0.4 m ² / Kg. (it is required from 2 to 2.5 Kg for 1 m ² of standard surface)
Diluyente	Water



100% Reciclado
Compromiso Medioambiental y Social Jafep



Repintado

From 6 hours

Secado

60 minutes approximately

Dónde aplicarlo

It is a stone coating suitable for exterior walls and wells, even with harsh weather. On interior walls for stair walls, offices, premises with high use, etc.

Productos relacionados

SELLACRYL

Modo de empleo

Surfaces must be clean, dry and free from corrosion, dust, grease, saltpetre, damp, etc. If the surface is hard or it is already painted, scraped and clean totally. Apply a first coat of Pétrex Liso (Smooth Pétrex) thinning down to 20-25% with water, and a second coat ready to use to get the desired rough effect, using the suitable trowel. In some cases, use primers such as Sellacryl (clear primer) or Sellaprim Exterior (Exterior white primer). Do not apply at temperatures below 5° C.

Formatos

Packaging: 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com