

Ficha Técnica

PINKEL STIPPLED EMULSION PAINT



Descripción

Emulsion for interiors. Brilliant white smooth finish. High level of resistance and washability. Especially designed to achieve, using just one product, decorative textured finishes: Stippled, striped, woven, etc.

Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Acrylic copolymers
Peso específico	1.70 gr./ cm

Datos de aplicación del producto

Rendimiento	Between 0.5 and 3 m ² /Kg. (depending on application)
Diluyente	Water
Secado	1 - 2 hours (touch dry), 24 - 48 hours (totally dry)



Dónde aplicarlo

Depending on type (brush, sponge, comb, etc.)

For decorating interiors using a large variety of textured finishes: stippled, woven, gotelé, etc. using in each case the appropriate items: sponge rollers, combs, spatulas, etc.

Productos relacionados

SELLACRYL
THIXOTROPIC SYNTHETIC SEALER

Modo de empleo

On clean new surfaces that are dry and free from rust, grease or saltpetre:

- Cement and concrete: Directly, using the required dilution for each type,
- Plaster, gypsums or wood: Fixing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With quality paintwork in good condition: Wash and seal using a gentle action and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 5° C.
- Do not expose the containers to extreme temperatures

Formatos

Plastic containers of: 4 litres; 18 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep