

Ficha Técnica

ROYAL EXTERIOR MATT EMULSION PAINT



Descripción

High quality emulsion produced using resins in an acrylic emulsion, with exceptional whiteness, coverage and performance. For perfect finishes on interiors and exteriors. It seals façades making them water-proof, while continuing to allow the surface to breath. It does not turn yellow and has a very low odour.

Datos técnicos

Datos de identificación del producto

Color	White and colours to order
Aspecto	Matt
Naturaleza	Pure acrylic
Peso específico	1.50 gr./cm ³

Datos de aplicación del producto

Rendimiento	8 - 10 m ² /litre and coat
Diluyente	Water



Repintado

6 - 8 hours

Secado

Touch dry in 30 minutes

Dónde aplicarlo

Brush, roller or spray (adjusting density).

It can be applied using a brush, roller or spray gun. On exterior surfaces with bases made of cement, concrete, fibre cement, etc. and on interior plastered, prefabricated, wood and metal surfaces that have been treated appropriately. All the surfaces should be clean, dry and free from grease and saltpetre. As it is a 100% acrylic product it has a high level of resistance to alkalis, and as a result it is also especially recommended for basements, cellars, garages, etc.

Modo de empleo

- New bases: The surfaces must be completely dry (plasters) or set (cements). Apply directly, but diluting the first coat by 10-15%. If it is very absorbent, seal prior to application. If there are defects in the base, fill with a suitable product or in the case of surfaces that are excessively polished, sand to make the surface porous.

- Restoration: If the surface is already painted and in good condition it can also be applied directly, but if not, the paint should be removed in order to proceed as per the instructions for new bases.

IMPORTANT: Also available is the ANTI-MILDEW type paint, which contains contrasting fungicides that are widely and totally effective.

- Do not apply at temperatures below 5 °C or above 35 °C.

- Do not expose the containers to extreme temperatures.

- Can be stored in the original sealed container for up to 3 years.

- Avoid adding water to the product, which should not be used in order to avoid product deterioration.

Formatos

Metal containers of: 3.5 Litres 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



100% Reciclado

Compromiso Medioambiental y Social Jafep



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com