

## Ficha Técnica

# SMOOTH SILICONED COATING



## Descripción

Exterior coating based on polysiloxane formulation. With good resistance to harsh weather, salpeter and abrasion. Waterproof and mouldproof. The polysiloxane provides a water-repellent effect as well, and make the permeability to water-vapour easier at the same time.

## Datos técnicos

### Datos de identificación del producto

Color	White and colours to order
Aspecto	Smooth matt
Naturaleza	Acrylic copolymers and polysiloxane resins
Peso específico	1.5 ± 0,5 gr./ cm3

### Datos de aplicación del producto

Rendimiento	From 10 to 12 m2/L, and coat (depending on the surfaces).
Diluyente	Water



Repintado

about 5h

Secado

45 minutes approximately

## Dónde aplicarlo

Brush, roller, spray or airless (adjust viscosity).

Exterior decoration and protection: Exterior walls, courtyards, etc. with an excellent quality finish and unbeatable washability and coverage.

## Modo de empleo

On exterior surfaces that are clean, dry and free from corrosion, grease, paint in bad condition or saltpetre

- Apply directly but thin down to 10% for the first coat. Then, apply a second coat with a slight thinning down.

- On old painted surfaces: Remove the paint in bad conditions using water under pressure and make the required repairs.

With mould, use bleach to remove them, rinse and dry.

General recommendations:

- Do not apply at temperatures below 5° C.

- Do not apply if it is possible to rain.

- Do not expose the packaging to extreme temperatures.

## Formatos

Metallic packaging: 15 litres.



Atención al Cliente

**967 44 05 96**

atencionalcliente@jafep.com



Servicio Técnico

dpto\_tecnico@jafep.com



ARGENTINA

DUBAI

ESPAÑA

MARRUECOS

POLONIA

UCRANIA



www.jafep.com  
jafep@jafep.com