

Ficha Técnica

SUPER 86 MATT EMULSION PAINT



Descripción

High quality paint produced using resins and pigments with a high level of resistance and fastness to light. It provides brilliant white washable finishes with excellent coverage.

Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Vinyl copolymers
Peso específico	1.54 gr./cm ³

Datos de aplicación del producto

Rendimiento	From 5 to 7 m ² /Kg. (depending on the surface)
Diluyente	Water
Repintado	From 2 - 4 hours



Secado

30 minutes approximately

Dónde aplicarlo

Brush, roller, spray gun or airless gun (adjusting density).

Painting and decorating interior and exterior masonry where a quality silk finish that is easy to apply and has a low odour is required.

Modo de empleo

On clean new surfaces that are dry and free from rust, grease or saltpetre:

- Cement and concrete: Directly, diluting by up to 15% for the first coat.
- Plaster, gypsums or wood: Fixing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With paints in good condition: Wash and sand to a smooth finish and apply as follows.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 7° C.
- Do not expose the containers to extreme temperatures

Formatos

Metal containers of: 750 ml; 4 litres; 8 litres; 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



ARGENTINA

DUBAI

ESPAÑA

MARRUECOS

POLONIA

UCRANIA



www.jafep.com
jafep@jafep.com