

Ficha Técnica

SUPER SATIN EMULSION PAINT



Descripción

High quality emulsion paint for interior and exterior use. High level of stability and resistance, which gives a water-proof and hard-wearing finish with excellent whiteness and good covering power. Final appearance satin / silk. Easy to wash.

Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Satin
Naturaleza	Resistant copolymer resins
Peso específico	1.25 gr./ cm

Datos de aplicación del producto

Rendimiento	5 - 8 m ² / kg.
Diluyente	Water
Repintado	After 6 hours



Secado

30 - 45 minutes (touch dry)

Dónde aplicarlo

Brush, roller, spray gun or airless gun (adjusting density)

Quality paint. Excellent results in terms of whiteness, coverage and washability on all types of surfaces, walls and ceilings, leaving a pleasing satin / silk appearance on both smooth and rough surfaces (gotelé, stippled, striped, etc.), and effective protection to exteriors.

Productos relacionados

THIXOTROPIC SYNTHETIC SEALER
SELLACRYL

Modo de empleo

On new surfaces that are clean, dry and free from rust and grease made of:

- Cement and concrete: Directly, diluting by up to 25% for the first coat.
- Plaster, gypsums or wood: Sealing prior to application with a Synthetic Sealer or with JAFEP Sellacryl.

On old painted surfaces:

- With quality paintwork in good condition: Wash and sand to a smooth finish and then apply.
- With paintwork in poor condition: Remove and proceed as per the instructions for new surfaces.
- On distempers, PVA or lime paints: Apply a base coat using a fixative or JAFEP Sellacryl.

In general, we recommend:

- Do not apply at temperatures below 7 °C.
- Do not expose the containers to extreme temperatures

Formatos

Metal containers of: 750 ml; 4 litres; 8 litres; 15 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com