

Ficha Técnica

Satin Alkyd Enamel

Synthetic enamel based on alkyd resins

Versión: 18/04/2023



Ventajas

- Excellent covering power.
- Easy to apply, does not sag, excellent leveling.

Descripción

It is a satin alkyd enamel with great covering power, formulated with special alkyd resins and pigments of proven resistance and stability to light, which provides top-quality finishing levels.

It is a product with the "high solids" technique, so it is recommended to apply thin layers and respect the drying and repainting times in order to obtain the best and maximum benefits.

Certificados de empresa



Datos técnicos

Datos de identificación del producto



Color	White and Black. RAL colours upon request.
Aspecto	Satin
Naturaleza	Alkyd resins
Peso específico	between 0,95gr./ cm ³ and 1,25 gr./cm ³ depending on colour.

Datos de aplicación del producto

Herramienta	Brush, roller, spray or airless
Espesor mínimo	45-50 microns dry
Rendimiento	12 - 14 m ² /L/layer
Repintado	24 hours
Secado	3 - 4 hours

Prestaciones finales

Resistencia al frote en húmedo	5
--------------------------------	---

Dónde aplicarlo

It is a high-quality satin synthetic enamel that meets the needs of professionals and individuals, being very suitable for decorating and protecting surfaces made of iron, steel, wood, plaster, etc., such as: doors, chairs, tables, windows, radiators, gates, metal structures, machinery, boats, etc.

Practical (actual) coverage will depend on film thickness, nature of the substrate and method of application.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current bottle with the next one at 50% to reduce the normal differences between batches.

Modo de empleo

Stir the contents of the container well. Apply by brush and roller at original viscosity. If applied by spray gun, adjust the viscosity with suitable thinners.



The surfaces must be clean and dry, free of rust, dust, grease, saltpeter, moisture, etc. Surfaces containing old paint must be scratched and cleaned in its entirety to ensure adherence to them.

When applying on wood and plaster, the surface must be previously prepared with Synthetic Sealer or our Multipurpose water-based. On iron and steel, the surface must be previously protected with Antioxidant Primer or Electrolytic Lead Minium. On galvanized steel and alloys, perform a suitable pretreatment.

As it is a high-solids product indoors, a single coat of Enamel may suffice.

Outside it is convenient to finish with 2 or 3 hands.

WARNING: Alkyd products may yellow slightly in the dark or on supports that reach high temperatures.

Almacenamiento

- In its original closed container, at non-extreme temperatures and humidity.
- Keep away from direct sunlight.
- Recommended maximum since manufacture: 2 years.

Formatos

Containers of: 125 ml; 375ml; 750 ml; 4 liters



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com