Ficha Técnica

WATER-BASED MATT FINISH EMULSION PAINT DUAL





Descripción

Matt paint with excellent whiteness and coverage. Washable and resistant. Particularly suitable for interior use, but with good performance in exterior use as well thanks to its outstanding resistance and stability.

Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Acrylic copolymers
Peso específico	1,55 gr./cm3

Datos de aplicación del producto



From 5 to 6 m2/Kg. (depending on surfaces)





Diluyente

Repintado

Secado

Water

From 2 - 4 hours

30 minutes approx

Dónde aplicarlo

Brush, roller, spray or airless (adjust viscosity).

Paint with high balance properties for a good performance on interior surfaces, walls and ceilings, with easy application and quick touch dry. It can be applied on exterior surfaces like a facade protector in non-extreme conditions.

Productos relacionados

Water-based Sealer THIXOTROPIC SYNTHETIC SEALER SELLACRYL

Modo de empleo

On surfaces that are clean, dry and free from corrosion, grease or saltpetre:

- Cement and concrete: Directly, thinning down the first coat 15% with water.
- Gypsum, plaster or wood: Prime previously with Selladora Sintética (Alkyd Sealer) or with Sellacryl JAFEP.

On painted surfaces:

- On good conditions and high quality paint: wash and sand softly and next, apply it.
- On bad conditions paint: remove it and proceed like a non-painted surface.
- On distempers, PVA and lime paints: Apply a primer or Sellacryl JAFEP.
- General recommendations:
- Do not apply at temperatures below 5° C.
- Do not expose the packaging to extreme temperatures.

Formatos

Metal packaging: 750 ml; 4 Litres; 8 Litres; 15 Litres









ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com jafep@jafep.com