

Ficha Técnica

Metallic Paint

Metallic Acrylic Paint

Versión: 04/05/2023



Descripción

Water-based acrylic paint with a metallic finish that is easy to apply and very good leveling. Washable and very covering. It offers extraordinary hardness and resistance to friction. We can achieve a smooth effect or a "woven" or backlit effect.

Propiedades

- Washable and very covering.
- Extraordinary hardness and resistance to friction.

Certificados de empresa



Datos técnicos



Datos de identificación del producto

Color	Gold, Silver & Copper
Aspecto	High Satin or Semi-Gloss
Naturaleza	Acrylic Copolymers

Datos de aplicación del producto

Herramienta	Paletina, Brush or Roller
Rendimiento	10 – 12 m ² /L/Coat
Diluyente	Diluyente para pinturas y esmaltes al agua
Repintado	6 hours
Secado	45 – 60 minutes

Prestaciones finales

Resistencia al frote en húmedo	Paletina, brush or roller
--------------------------------	---------------------------

Dónde aplicarlo

Applicable both indoors and outdoors. Very suitable for the decoration and protection of masonry surfaces, wood, plaster, etc.

Precauciones

- Do not apply at temperatures below 5°C or above 30°C.
- Do not apply with risk of frost or rain.
- Do not apply in conditions of strong winds or in direct sunlight.
- Avoid using different batches in the same cloth or, failing that, mix the current can with the next at 50% to reduce the normal differences between batches.

Productos relacionados

[SELLACRYL](#)



Modo de empleo

ON NEW, CLEAN, DRY SURFACES FREE OF RUST, GREASE OR SALTPETER OF:

- Cement and concrete: Once set. Directly, diluting up to 10% for the first coat.
- Plaster, plaster or wood: Fixing or sealing previously with products suitable for each case. Diluting up to 10% in the first coat.

ON OLD PAINTED SURFACES:

- With paints in good quality condition: Wash and sand lightly, putty if necessary and apply afterwards.
- With paintings in poor condition: Remove and proceed as a new surface. If alkalinity is detected on the support, it must be corrected.

Almacenamiento

- In its original closed container, at non-extreme temperature and humidity.
- Keep out of direct sunlight.
- Maximum recommended since manufacture: 2 years.

Formatos

1L Plastic Pot



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com

