

Ficha Técnica

DECORATIVE EFFECT MATT UNDERCOAT)



Descripción

Acrylic coating developed to be the ideal undercoat for the finish coat of most of our Decorative Effect Paints. It is washable and breathable and an excellent coverage.

Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Acrylic copolymer
Peso específico	1.6 ± 0,5 gr./ cm3

Datos de aplicación del producto

Rendimiento	From 5 to 8 m2/Kg. (depending on the surface)
Diluyente	Water
Repintado	After 5 hours



100% Reciclado

Compromiso Medioambiental y Social Jafep



Secado

30 minutes approximately

Dónde aplicarlo

Brush, roller, spray gun or airless (Adjust viscosity)

Apply a first coat of Fondo (Undercoat) thinning down to 20% with water and a second coat with the same thinning if necessary. Let dry four hours between every coat. It can be apply by brush, roller or spray.

Productos relacionados

THIXOTROPIC SYNTHETIC SEALER
SELLACRYL

Modo de empleo

On all kind of surfaces that are clean, dry and free from corrosion, grease or salpêtre:

- Prime previously with Selladora Sintética (Alkyd Sealer) or Sellacryl JAFEP (Clear Primer), duly thinning down.

On old painted surfaces:

- On painted surface in good condition, and quality: Wash and sand softly. Then apply it.

- On painted surface in bad condition: Remove and proceed like a new surface.

- On distempers, PVA or lime paints: Apply a primer undercoat or Sellacryl JAFEP.

General recommendations:

- Do not apply at temperatures below 5° C.

- Do not expose the packaging to extreme temperatures.

Formatos

Plastic packaging : 5 Kgs.



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com