

Ficha Técnica

JAFELAC SEMI-MATT NITROCELLULOSE LACQUER



Descripción

Colourless transparent lacquer made from alkydic resins combined with nitrocellulose resins laminated with a good balance of elasticity, adhesion and durability.

Datos técnicos

Datos de identificación del producto

Color	Colourless
Aspecto	Semi-matt
Naturaleza	Alkydic combined with nitrocellulose
Peso específico	1.0 gr./ cm ³ approximately

Datos de aplicación del producto

Diluyente	Nitrocellulose solvent
Repintado	24-48 hours



Secado

Touch-dry in approximately 1 hours

Dónde aplicarlo

Essentially by brush.

For protecting and decorating interior wooden surfaces, doors, windows, railings, etc.

Modo de empleo

New wood: Clean, sand and remove dust. Apply a first coat of cellulose base, which once completely dry should be sanded as required.

Varnished or polished woods: It should be cleaned and sanded if in good condition. If in poor condition all of the existing varnish should be removed. A test to check the compatibility with previous coats should be performed.

Clean utensils with nitrocellulose solvents.

Formatos

Metal containers of: 1 Litre; 5 Litres; 20 Litres



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA

DUBAI

ESPAÑA

MARRUECOS

POLONIA

UCRANIA



www.jafep.com
jafep@jafep.com