

Ficha Técnica

JAFESTUC LIME PLASTER



Descripción

Decorative covering for interiors, to be applied to plastered walls and ceilings, gypsum and similar plasters, which by using the spatula technique achieves beautiful effects.

Datos técnicos

Datos de identificación del producto

Color	White and base colours
Aspecto	Brilliant finish when polished
Naturaleza	Acrylic copolymers
Peso específico	1.60 gr./cm ³

Datos de aplicación del producto

Rendimiento	2 - 3 m ² /kg.
Secado	6 - 8 hours



100% Reciclado
Compromiso Medioambiental y Social Jafep



Dónde aplicarlo

Spatula and stainless steel trowel.

On plaster, gypsum, etc. bases that are clean, dry and free from dust and grease.

Modo de empleo

The surface must be even, if not, plaster to create a smooth finish with very little absorption. Prime thoroughly using a product such as the Petrex 5 Plain Coating, diluted and coloured using the required shade for the plaster. Stir vigorously before spreading the product using a trowel or spatula, always using strokes in the same direction. Leave to dry, sanding out the imperfections (280 grade minimum). This can be repeated several times. Once dried, sand the entire surface using sanding sheets (500 grade). Clean and remove dust. Achieve the final pattern with successive separate touches, getting rid of any excess product and filling in any holes. The natural shine will appear by rubbing and polishing using the trowel or spatula with which it is applied.

Formatos

Plastic containers of: 1 Kg.; 5 Kg.; 25 Kg.



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

100% Reciclado



ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA

www.jafep.com
jafep@jafep.com