

Ficha Técnica

MURALIA UNDERCOATING



Descripción

Plastic putty in paste form, ready to use, for apply with trowel or brush and get a rustiuc surface with a very easy application.

Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Vinilyc copolymers
Peso específico	1.25 gr./cm3

Datos de aplicación del producto

Rendimiento	1,3 Kg / m2
Secado	6 - 8 hours



100% Reciclado
Compromiso Medioambiental y Social Jafep



Dónde aplicarlo

Trowel.

To apply Muralla Undercoating use a plastering trowel. Render surfaces roughly to a desired thickness and texture by keeping the trowel parallel to the wall. Different effects can be obtained by using a brush. In this application it must be diluted with water between 12-15% and the coverage is greater.

Modo de empleo

To non-painted surfaces: First apply an emulsion undercoat to obtain a surface with a uniform absorption rate.

Painted surface: To healthy painted surfaces apply Muralla Undercoating directly. Unfit and unhealthy surfaces should be treated as non-painted surfaces.

Formatos

Plastic containers of: 5 and 20 Kg.



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA

DUBAI

ESPAÑA

MARRUECOS

POLONIA

UCRANIA



www.jafep.com
jafep@jafep.com