

Ficha Técnica

Matt Pinroda Acrylic Paint



Descripción

Plastic paint for interiors of great whiteness and good coverage with an unbeatable quality/price ratio.

Certificados de empresa



Datos técnicos

Datos de identificación del producto

Color	White
Aspecto	Matt
Naturaleza	Acrylic Copolymers



Peso específico 1.70 gr./cm³ approximately

Datos de aplicación del producto

Herramienta	Brush, Roller, Gun or Airless
Rendimiento	6 - 9 m ² /L/Coat
Diluyente	Water
Repintado	6 - 7 hours
Secado	30 minutes

Prestaciones finales

Resistencia al frote en húmedo Class 5 (Standard UNE-EN 13300); >300 cycles (UNE 48243)

Dónde aplicarlo

Brush, roller or spray gun (adjusting viscosity).

Economic paint for interiors, suitable for painting ceilings, with good performance, whiteness and coverage.

Precauciones

- Do not apply at temperatures below 5 °C nor above 30 °C.
- Do not apply with risk of frost or rain.
- Do not apply in strong winds or under direct sun.
- Avoid using different batches on the same cloth or, failing that, mix the current pot with the next one at 50% to reduce the normal differences between batches.

Productos relacionados

SELLACRYL
DECORATIVE EFFECT MATT UNDERCOAT)

Modo de empleo

On all types of very clean, degreased and dry surfaces:



- New Surfaces: Apply directly, diluting up to 25% for the first layer.
- Old surfaces with paint in good condition: Wash and sand beforehand.
- Old surfaces with paint in poor condition: Scrape and proceed as a new surface.
- On tempera, glue or lime paints, even sanded: First apply a fixing primer or Sellacril JAFEP.

In general it is recommended:

- Do not apply at temperatures below 5° C.
- Do not expose the containers to extreme temperatures.

Practical (actual) coverage will depend on film thickness, nature of substrate and method of application.

Almacenamiento

- In its original closed container, at not extreme temperature and humidity.
- Keep away from direct sunlight.
- Maximum recommended since manufacturing: 2 years.

Formatos

Containers of: 3 liters (5 Kg) and 13 liters (22 Kg)



Atención al Cliente

967 44 05 96

atencionalcliente@jafep.com



Servicio Técnico

dpto_tecnico@jafep.com



Compromiso Medioambiental y Social Jafep

ARGENTINA DUBAI ESPAÑA MARRUECOS POLONIA UCRANIA



www.jafep.com
jafep@jafep.com